neroo®

www.neroo.eu



PLUG-IN INDOOR SIREN

PlugAlert

User manual

Last updated: 17 November 2026

Welcome

Thank you for choosing the PlugAlert.

The PlugAlert is a wireless indoor siren with a strobe light that you simply plug into a wall socket. When your alarm panel raises the alarm, it sounds a loud alarm signal and the red light flashes brightly. Handy in a room away from your alarm panel, such as the bedroom or the top of the stairs, so you always hear an alarm.

The PlugAlert always stays plugged in. The built-in battery is only a backup: if the power fails, it keeps working for up to 12 hours. The PlugAlert works with the ShieldLink Lite, Plus, Pro and Elite and with the CamperGuard Pro.

Contents

1 The PlugAlert at a glance 2
2 Switching on 2
3 Pairing with your alarm panel 3
4 The right spot 4
5 Unpairing and factory settings 4
6 Battery and power cuts 4
7 Specifications 5
8 Warranty & support 5

1 The PlugAlert at a glance



PlugAlert: red strobe light on the front, plug on the back

Part	What it does
Red strobe light	Flashes during an alarm, and when pairing and setting up
Siren	Sounds a loud alarm signal and the beeps during pairing
SET button (round, bottom of the front)	For pairing with your alarm panel and clearing pairings
Battery switch (back)	Switches the backup battery on or off; it takes over if the power fails
Plug	For a standard wall socket (100–240 V); the PlugAlert has no on/off button

2 Switching on

1. Set the battery switch on the back to ON. The PlugAlert is now running on its battery, so you can pair it without a wall socket.
2. Pair it with your alarm panel (chapter 3).
3. Then plug the PlugAlert into its permanent socket. The battery recharges there.

IMPORTANT

Always leave the PlugAlert plugged in: that is where it gets its power. The battery is only meant as a backup in case of a power cut, not for using the PlugAlert unplugged.

3 Pairing with your alarm panel

Pair the PlugAlert next to your alarm panel. It does not need to be plugged in for this: the battery switch set to ON is enough. Then plug it into its permanent socket.

1. On your alarm panel, open the menu for pairing a siren — see the table below.
2. Hold the SET button on the PlugAlert for 3 seconds, until you hear 1 short beep and the light stays on. It is now in pairing mode for 20 seconds.
3. Within those 20 seconds, let your alarm panel send the pairing signal (see the table).
4. Do you hear 1 short beep and does the light go out? Then the PlugAlert is paired.

Alarm panel	How to send the pairing signal
ShieldLink Pro, Elite and CamperGuard Pro	Tap Connection (user code, default 1234) → Siren. Put the PlugAlert in pairing mode, then press OK on the panel.
ShieldLink Plus	Menu → Accessories (user code, default 1234) → Siren. Put the PlugAlert in pairing mode, then confirm on the panel.
ShieldLink Lite	Put the PlugAlert in pairing mode and trigger an SOS alarm within 20 seconds, for example with the SOS button on your QuickLink. Then switch the alarm off.

You hear	You see	Meaning
1 short beep	Light goes out	Paired
3 short beeps	Light flashes 3 times quickly	This PlugAlert was already paired with this panel
No beep	Light goes out	After 20 seconds without a signal, pairing mode stops by itself — try again

Pairing does not work?

- Keep the PlugAlert close to your alarm panel while pairing, and check that the battery switch is set to ON.
- Mind the 20 seconds: open the pairing menu on your alarm panel first, and only then put the PlugAlert in pairing mode.
- Still not working? Reset the PlugAlert to factory settings: hold the SET button for 10 seconds, until you hear 3 long beeps and the light flashes 3 times. All old pairings are then cleared. Then pair it again.

GOOD TO KNOW

Test the pairing with the siren beep: on your alarm panel, switch on the option External siren beep (Pro, Elite and CamperGuard: Security → Alarm · Plus: Menu → Security → Alarm · Lite: in the app under Settings). Arm and disarm the system: the PlugAlert then beeps briefly along. Switch the beep off again after the test.

4 The right spot

- Somewhere you can hear the alarm well, such as the bedroom, the landing or a room far away from your alarm panel.
- In a socket that always has power: not in a power strip with a switch or in a timer.
- In plain view, not behind a sofa or cupboard: then the strobe light is easy to see and the siren is at its loudest.
- Within range of your alarm panel: up to 120 metres in open field, less through walls and floors.
- Indoors only, in a dry place.

GOOD TO KNOW

Two PlugAlerts in the house? Pair both with your alarm panel: they will then go off together.

5 Unpairing and factory settings

Want to pair the PlugAlert with a different alarm panel, or does pairing not work? Then reset it to factory settings. This clears all pairings.

1. Hold the SET button for 10 seconds.
2. You hear 3 long beeps and the light flashes 3 times: all pairings are cleared.
3. Then pair the PlugAlert again, as in chapter 3.

IMPORTANT

Also remove the siren in the app or on your alarm panel if you no longer use it.

6 Battery and power cuts

The PlugAlert runs on mains power from the socket, which also keeps its battery charged. The battery is only a backup: if the power fails and the battery switch is set to ON, the PlugAlert keeps working for up to 12 hours. As soon as the power is back, the battery recharges by itself.

- So always leave the PlugAlert plugged in, even when you are not using the alarm.
- Unplugging it to put it away? Then set the battery switch to OFF, otherwise the battery runs flat.
- Set the battery switch back to ON when you use it again.

7 Specifications

Type	Wireless indoor siren with strobe light, for a wall socket
Works with	ShieldLink Lite, Plus, Pro and Elite · CamperGuard Pro
Wireless	433 MHz (EV1527) · range up to 120 m in open field
Power supply	100–240 V AC (wall socket)
Battery	3.7 V / 500 mAh, built in · backup up to 12 hours during a power cut
Power consumption	Standby < 10 mA · alarm < 200 mA
Dimensions	90 × 90 × 45 mm
Use	Indoors only
In the box	PlugAlert

8 Warranty & support

Your PlugAlert comes with a manufacturer's warranty. Questions or need help? Our team is happy to help.

- E-mail: service@neroo.nl · Phone: +31 85 850 0107
- Manuals, videos and frequently asked questions: neroo.eu/pages/manuals
- End of its life? Hand the siren in at a collection point for electrical appliances (WEEE): the battery is built in.

© 2026 Neroo. All rights reserved.